



**PRODUCT DATA SHEET: SUPER TRACTOR OIL 15W-40**

**SUPER TRACTOR OIL 15W-40** is a high quality so called “Super Tractor Oil Universal”(STOU) lubricant formulated with carefully selected mineral base stocks and modern additives.

**SUPER TRACTOR OIL 15W-40** has been developed for use in tractors, combines harvesters and off road machinery with naturally aspirated or turbo charged diesel engines. Furthermore the product has been designed to serve in the hydraulic system, lubricate the transmission and power take off, final drive and oil immersed “wet brakes”.

**SUPER TRACTOR OIL 15W-40** possesses viscosimetric characteristics allowing excellent cold starting in winter time and optimal response of the hydraulics under all conditions.

**SUPER TRACTOR OIL 15W-40** ensures optimal protection of the engine, effectively preventing wear and sludge; apart of that the product shows superior performance in transmissions of off road equipment.

TYPICAL PROPERTIES:		SPECIFICATIONS:
PRODUCT CODE	64302	Exceeds: API CF-4/CF/SF, API GL-4 John Deere J27C, MF 1139/1144 FORD M2C-159B Allison C-4 Caterpillar TO-2 ZF TE-ML 06B/06C/07B
SAE	15W-40	
DENSITY @ 15°C	884 kg/m <sup>3</sup>	
VISCOSITY @ 100°C	14.4 mm <sup>2</sup> /s	
FLASH POINT	220°C	
POUR POINT	-30°C	